



## DESCRIPTION

Pigtail E2000™, APC 8°, RdM connector, Grade B/1, green  
Green Singlemode OS2 G.657A, 900µm LSZH jacket  
Semi-tight buffer, strippability > 1.0m  
Buffer and fiber coating in the same color

## SPECIFICATIONS

Cable type	Pigtail	
Fiber type	Singlemode (SM)	
Outer sheath material	LSZH	
Conductor type FO	dry semi-tight buffer, strippability > 1.5m	
Fiber class	G.657.A1 (Corning SMF-28e+R), G.657.A2	
Fiber diameter	E09 / 125 µm	
Cable overall diameter	900µm	
Connector type (A)	E-2000™ <b>R&amp;M</b>	
Connector color (A)	Green	
Lever- / frame-coding (A)	Color	
Lever color (A)	Green	
Polishing plug (A)	APC 8°	
Protection class IP (A)	IP 20	
Return loss grade RL (A)	1	acc. to IEC 61300-3-6
Attenuation grade IL (A)	B	acc. to IEC 61300-3-34
Connector class	Connector	
Standard	E-2000™ (LSH) connector acc. to IEC 61754-15 and EN 186270	

### Coloures

red, green, blue,  
yellow, white, gray,  
brown, violet,  
turquoise, black  
orange and pink

### Cable sheath characteristics

Buffer and fiber coating in the same color  
Cable, metal-free  
Zero-halogen

Address: 2730 Simitli, Bulgaria  
Multifunctional zone, distr. 14,  
Contact number: +359 882 509 661  
[www.cimlercable.com](http://www.cimlercable.com)  
[sales@cimlercable.com](mailto:sales@cimlercable.com)